



Order no.: 052524

Platform ladder FlexxStep

/

Number of rungs

4

5

6

Specification

| Working height 3 m | Step design Rungs | Number of steps/rungs 4 rungs | Platform included as step Yes | Platform height 1.02 m |
|-------------------------------------------------------|------------------------------------------------|-------------------------------|---------------------------------------------------------------|----------------------------------|
| Platform length 655 mm | Platform width 480 mm | Step/Rung height 30 mm | Step depth 30 mm | Step/Rung distance 280 mm |
| Base spread 1.15 m | Inclination 70° | Outer width 672 mm | Width incl. extension arm 1.64 m | Depth of side-rails 58 mm |
| Width of side-rails 25 mm | Castor diameter 150 mm | Max. load capacity 150 kg | Design type Freestanding Single-sided access With castors | Weight 27 kg |
| Transport dimensions 2420 x 770 x 390 mm, 27 kg | Business division MUNK Günzburger Steigtechnik | Order no. 052524 | Price € 1,348.00 | |

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails



- Rectangular rungs grooved on both sides, 30 x 30 mm
- Spacious platform made of grooved aluminium chequered plate 480 x 655 mm
- 4-fold edged rung-to-side-rail connection
- With handrail on both sides, 3-sided, 1,000 mm high railing with knee and foot rails
- Infinitely variably adjustable outriggers on both sides
- Automatically closing safety door
- Generous sized tool tray
- Two Ø 150 mm castors and practical folding mechanism for quickly moving to a new location
- Available with and without flexible telescopic push-fit attachment
- Design compliant DIN EN 131-7 and the French standards NFP 93-352/353
- Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Handrail (enclosed separately): 2 x

Castor (enclosed separately): 2 x

Security door: 1 x

Installation material: 1 x

Assembly instructions: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size



- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



More product pictures









Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place





Corporate certifications

on sustainability criteria









