



Order no.: 052534

## FlexxStep platform ladder 4 rungs with telescopic attachment 2 rungs



Number of rungs

- 4 + 2
- 5 + 2
- 5 + 3
- 6 + 2
- 6 + 3

### Specification

|   |  |  |   |                                     |
|---|--|--|---|-------------------------------------|
| Step design<br><b>Rungs</b>                               | Number of steps/rungs<br><b>4 + 2 rungs</b>                | Platform included as step<br><b>Yes</b>                  | Platform height<br><b>1.58 m</b>  | Step/Rung height<br><b>30 mm</b>    |
| Step depth<br><b>30 mm</b>                                | Step/Rung distance<br><b>280 mm</b>                        | Inclination<br><b>70 °</b>                               | Outer width<br><b>672 mm</b>  | Depth of side-rails<br><b>58 mm</b> |
| Width of side-rails<br><b>25 mm</b>                       | Castor diameter<br><b>150 mm</b>                           | Max. load capacity<br><b>150 kg</b>                      | Design type<br><b>Free-standing   Single-sided access   With castors   Flexible</b> | Weight<br><b>33 kg</b>              |
| Transport dimensions<br><b>2420 x 770 x 390 mm, 27 kg</b> | Transport dimensions 2<br><b>1145 x 565 x 105 mm, 6 kg</b> | Business division<br><b>MUNK Günzburger Steigtechnik</b> | Order no.<br><b>052534</b>  | Price<br><b>€ 1,700.00</b>          |

### Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- Spacious platform made of grooved aluminium chequered plate 480 x 655 mm

- 4-fold edged rung-to-side-rail connection
- With handrail on both sides, 3-sided, 1,000 mm high railing with knee and foot rails
- Infinitely variably adjustable outriggers on both sides
- Automatically closing safety door
- Generous sized tool tray
- Integrated Ø 150 mm castors and practical folding mechanism for quickly moving to a new location
- Design compliant DIN EN 131-7 and the French standards NFP 93-352/353
- Height-adjustable and suitable for stairs by means of telescopic outrigger that can be mounted without tools
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



### Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

