



Order no.: 021714

2-section rung rope-extension ladder with standard stabiliser



Number of rungs

2x14

2x16

2x18

2x20

Specification

Working height 8.3 m	Step design Rungs	Number of steps/rungs 2x 14 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Retracted length 4.18 m	Extended length 7.22 m	Outer width 420 mm	Stabiliser width 1.2 m
Depth of side-rails 73 mm	Width of side-rails 25 mm	Design type To lean against 2-part	Weight 22.2 kg	Transport dimensions 4125 x 445 x 169 mm, 22.2 kg
Business division MUNK Günzburger Steigtechnik	Article no. 021714	Price € 780.00		

Facts

- Rung rope-extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection

- Convenient height adjustment from rung to rung thanks to two pulleys with plastic cable
- Upper ladder with wall wheels
- Corrosion-resistant guide fixtures with sliding guides
- Rung distance: 280 mm
- Ladder width: 470 mm (without stabiliser)
- Maximum load: 150 kg
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting

- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part




roll-bar retrofit kit


- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down




Accessories




Order no.: 019326
Accessory package "TRBS kit"




Order no.: 019324
Accessory package "Secure footing"





Order no.: 019329
Accessory package "Ergonomics"





Order no.: 019328
Accessory package "Practical aids 2"





Order no.: 019309
Accessory package "Ladder head protection, complete set"





Order no.: 019315
Ladder head protection





Order no.: 019316
Ladder head protection





Order no.: 019317
Ladder head protection





Order no.: 019319
Ladder head protection, gutter





Order no.: 019318
Ladder head protection, beam





Order no.: 040344
Ladder head protection, magnet





Order no.: 019310
Ladder head protection, rung and step hole

















Order no.: 019311
Ladder head protection, rung and step hole



Order no.: 019312
Ladder head protection, rung and step hole



Order no.: 019634
'roll-bar' retrofit kit





Order no.: 019175
Inspection sticker



Order no.: 030296
Push-fit handrail for rung/step spacing 280/263 mm



Order no.: 030297
Push-fit handrail for rung/step spacing 280/263 mm



Order no.: 019254
Guide fixture, upper, for push-up extension, rope-extension and multi-purpose ladders



Order no.: 019257
Guide fixture, lower, for 2-section rope-extension ladders




Order no.: 019424
Locking hook, complete, 73 x 25 mm

Spare parts



Order no.: 019632
Stabiliser complete



Order no.: 019772
Complete castor unit



Order no.: 019686
Pulley For 2- and 3-section rope-extension ladders



Order no.: 019199
Outside shoe for cross-tube



Order no.: 019144
Information stickers for push-up extension and rope-extension ladders over 3 m

Certificates



17KFP1539-03 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-
3:2007
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK
EK5/AK1 17-1:2017
DIN EN 131-1:2016
DIN EN 131-2:2017

Corporate certifications

on sustainability criteria

