

Order no.: 032121

## Telescopic ladder 4-section with stabiliser



Number of rungs

4x3

4x4

4x5

4x6

### Specification

|   |                                     |   |  |  |
|---|-------------------------------------|---|--|--|
| Working height min.<br><b>3.05 m</b>                          | Working height max.<br><b>4.2 m</b> | Number of steps/rungs<br><b>4x 3 rungs</b>                | Step/Rung height<br><b>30 mm</b>                         | Step depth<br><b>30 mm</b>                                   |
| Step/Rung distance<br><b>280 mm</b>                           | Step design<br><b>Rungs</b>         | Ladder length as straight ladder (min.)<br><b>1.95 m</b>  | Ladder length as straight ladder<br><b>3.1 m</b>         | Ladder length as double-sided ladder (min.)<br><b>980 mm</b> |
| Ladder length as double-sided ladder<br><b>1.5 m</b>          | Outer width<br><b>370 mm</b>        | Stabiliser width<br><b>700 mm</b>                         | Width of side-rails<br><b>25 mm</b>                      | Max. load capacity<br><b>150 kg</b>                          |
| Design type<br><b>Flexible   4-part   Suitable for stairs</b> | Weight<br><b>12 kg</b>              | Transport dimensions<br><b>1000 x 425 x 196 mm, 12 kg</b> | Business division<br><b>MUNK Günzburger Steigtechnik</b> | Article no.<br><b>032121</b>                                 |
| Price<br><b>€ 534.00</b>                                      |                                     |   |  |  |

### Facts

- Aluminium telescopic rung ladder
- Stable rectangular tube side-rails

- Rectangular rungs grooved on both sides, 30 x 30 mm
- High-strength rung-to-side-rail connection
- Can be used as a step and straight ladder
- Can be used on stairs
- Folding in the middle by automatically locking steel hinges
- Both outer sections are telescopic from rung to rung
- Rung distance: 280 mm
- Ladder width: 370 mm
- Maximum load: 150 kg
- These products are covered by the statutory warranty
- Note: In accordance with TRBS 2121 Part 2, a suitable accessory is required for working on this ladder

### Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting

- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Easy handling

- Centrally mounted, automatically locking steel hinges for quick change of functions
- With Telesteps: Sturdy joints on folding units guarantee durability



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



### Flexible use

- Various application options
- Can be used as a height-adjustable step and straight ladder



### Ratchet handles

- Easy to handle thanks to ergonomic shape
- Stable and safe thanks to steel core and aluminium cover



### practical and compact

- Thanks to the telescopic function, the ladders can be folded/moved together to take up minimum space when not in use
- Space-saving storage and easy transport

### Height adjustment

- The height-adjustable ladder sections are ideal for use on stairs
- Intuitive telescoping of the ladder through clearly visible levers or ratchet handles



### **Safe standing**

- Stabilisers in optimum widths for the ladder model
- Conical construction (without stabiliser) or bevelled rubber shoes



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

