



Order no.: 111002

# Scaling ladder upper section DIN EN 1147, photoluminescent

Rung covering

Glow (yellow luminescent)

Standard (red)

## **Specification**

| Rescue height<br>1.6 m       | Intended use Rescue                     | Ladder length 2.7 m              | Ladder length, 4 scaling ladders <b>8.4 m</b>       | Setting angle 70 °                           |
|------------------------------|---|----------------------------------|---|--|
| Outer width <b>575 mm</b>    | Ladder feet<br><b>Ladder shoe</b>       | Depth of side-rails <b>74 mm</b> | Width of side-rails<br>35 mm                        | Step/Rung height 28 mm                       |
| Step depth<br>29 mm          | Number of steps/rungs <b>7 rungs</b>    | Step/Rung distance<br>273 mm     | Max. load capacity 216 kg                           | Persons max.<br>2                            |
| Material<br><b>Aluminium</b> | Rung covering Glow (yellow luminescent) | Weight<br><b>9.8 kg</b>          | Transport dimensions<br>84 x 567 x 2658<br>mm, 6 kg | Business division<br>MUNK<br>Rettungstechnik |
| Order no.<br><b>111002</b>   |   |                                  |   |  |

### **Facts**

- Rescue ladder compliant with DIN EN 1147
- Made of aluminium



- Secure push-fit connections with springloaded locking pin
- Conical side-rail guide for safe stance
- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 216 kg / 2 people
- Side-rails and rungs made of high-strength aluminium
- With yellow luminescent, heat-insulating and non-slip plastic covering
- 4-fold edged rung-to-side-rail connection
- Non-slip and replaceable ladder shoes

### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



# More product pictures





# **Corporate certifications**

on sustainability criteria









